



FAIR DINKUM SOLAR PUMPS

WATERBOY 4C5122200 4" Centrifugal Solar Pumping System

FEATURES

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

BENEFITS

- Lift up to 90m
- Flow rate up to 28,800 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

4C5122200

TDH	L/Min	L/Day
10	80	28,800
20	75	27,000
30	70	25,200
40	63	22,680
50	57	20,520
60	50	18,000
70	40	14,400
80	32	11,520
90	26	9,360


Complete & ready to install

Bore part number: 4C5122200-B40 / Dam Floating part number: 4C5122200-D40


Each Waterboy solar pump system includes:



4CSS5-12 pump, motor, controller



Heavy Duty Cyclone Rated Pole Mount Frame



8x275w (2.2kW total) Mono Crystalline Solar Panels



Bore Cap or Dam Float



40m of Power Cable low water probe & safety cabling



Low water protection (bore kit only)

Accessories

- 6101 - Tank switch
- 6045NO - Pressure switch
- 6112 - 1.5" Double acting float valve
- 6015 - Sacrificial anode 1 1/4"



Tank full switch inc 20m cable \$110+GST



Pressure Switch 12 bar inc gauge & fittings \$250+GST



Double acting float valve For use with Pressure Switch - \$220+GST



Anode \$110+GST



Shipping Dimensions
1x Crate 290 x 55 x 65cm @ 230kg
1x pallet 170 x 115 x 43cm @ 170kg